
BACKYARD RAIN GARDEN

RAIN GARDEN SITE REQUIREMENTS

1. DISTANCE TO BUILDING FOUNDATION:(10 FEET MINIMUM)			
2. DISTANCE TO SEPTIC SYSTEM DRAINFIELD:(25 FEET MINIMUM)			
3. DISTANCE TO WELL HEAD:(25 FEET MINIMUM)			
4. UPSLOPE DOWNSLOPE FROM WELL HEAD (CIRCLE ONE, DOWNSLOPE RECOMMENDED)			
5. UPSLOPE DOWNSLOPE LATERAL TO SEPTIC DRAINFIELD (CIRCLE ONE, LATERAL RECOMMENDED)			
6. SUN EXPOSURE IS FULL PARTIAL (CIRCLE ONE)			
7. DEPTH TO SEASONAL HIGH WATER TABLE: (> 30 INCHES RECOMMENDED)			
SOIL DATA			
1. PREDOMINANT SOIL TYPE: (FROM SOIL SURVEY)			
2. POST RAINFALL CONDITION OF PROPOSED RAIN GARDEN LOCATION ACCORDING TO LANDOWNER: WET OR SATURATED 1.5 DAYS AFTER RAINFALL? IF YES, SELECT ALTERNATE SITE.			
3. DEPTH TO WETLAND SOILS IN 24-INCH DEPTH TEST PIT: INCHES IF WETLAND SOILS (GREY WITH RIBBONS OF BROWN) ARE OBSERVED WITHIN 12 INCHES OF SURFACE, SITE IS UNSUITABLE FOR RAIN GARDEN.			
4. IS WATER PRESENT IN TEST PIT, 2 DAYS AFTER COMPLETE FILLING WITH WATER? YES NO (CIRCLE ONE)			
ANY WATER PRESENT WITHOUT ADDITIONAL RAINFALL INDICATES POORLY DRAINED SITE. IF PIT DRAINS COMPLETELY, REFILL AND CHECK AFTER 12 HOURS. A COMPLETELY DRAINED PIT CHARACTERIZES A WELL DRAINED SITE.			
RUNOFF VOLUME			
TOTAL WATERSHED AREA (A) = SQUARE FEET			
AREA OF CONNECTED IMPERVIOUS SURFACES (Ai) = SQUARE FEET			
CONNECTED IMPERVIOUS PERCENTAGE OF WATERSHED (I) = (Ai/A)*100=			
RUNOFF COEFFICIENT (Rv) = 0.05 + (0.009 *I) =			
STORM PRECIPITATION (P):(1.5 INCHES FOR CAMA COUNTIES, 1.0 INCH FOR ALL OTHERS)			
RUNOFF VOLUME (V) = Rv * A * (P/12) = CUBIC FEET**			
** REFER TO APPENDIX D OF CCAP STORMWATER BMP DESIGN MANUAL FOR RAIN GARDEN SIZING CHARTS.			

SITE MAP

SCALE: _____



RAIN GARDEN SIZE		
RAIN GARDEN PONDING DEPTH (Dp):	(3, 6 OR 9-INCHES RECOMMENDE	ED)
SURFACE AREA = RUNOFF VOLUME (V) / PONDING DEP	TH (FEET) = V/(Dp/12) =	SQUARE FEET
NOTE: BOTTOM OF RAIN GARDEN MAY HAVE VARYING HOURS. GRADE BOTTOM WITH ZONES AT DIFFERENT E THAT CANNOT TOLERATE WET CONDITIONS FOR EXTEI REQUIRED SURFACE AREA. FOR EXAMPLE, 50% OF CE THE AVERAGE DEPTH IS 7.5-INCHES.	ELEVATIONS TO IMPROVE SURVIVAL OI NDED PERIODS. DETERMINE AVERAGE	F BIORETENTION PLANTS E DEPTH TO CALCULATE
PEAK STORMWATER RUNOFF USING RATIONAL METHO	D	
C = RUNOFF COEFFICIENT = [(CONNECTED IMPERVIOUS	S AREA x 0.95) + (PERVIOUS AREA x 0.2	25)] / DRAINAGE AREA=
I = STORM INTENSITY (10-YEAR STORM EVENT, 5-MINUT MANUAL = INCHES/HOUR	E DURATION) FROM TABLE 3.1 OF CCA	AP BMP DESIGN
A = WATERSHED AREA DRAINING INTO BMP =	ACRES	NOTE: LOCATE ALL INLET AND OUTLET LOCATION(S)
PEAK FLOW FROM WATERSHED DURING 10-YEAR STOR	M EVENT = Q = C x I x A	MARK ANY ZONES OF VARYING BOTTOM ELEVATIONS
Q = PEAK FLOW = CUBIC FEET PER	SECOND	PLAN
		NOT TO SCALE
OUTLET WEIR DESIGN		
Cw = WEIR COEFFICIENT = 3.0		
H = HEIGHT OF WATER OVER TOP OF WEIR =	FEET (0.5 FEET MAXIM	
Q = PEAK FLOW = CUBIC FEET P	ER SECOND	TOP OF BERM ELEVATION =FEETFEETFEETFEET
L = LENGTH OF WEIR = Q / (Cw x H) =FEET		
		Dp = PONDING DEPTH =INCHESINCHES
NOTES:		BOTTOM ELEVATION =FEET
		CROSS SECTION
		NOT TO SCALE
		WARNING:
		LOCATE ALL UNDERGROUND UTILITIES BEFORE DIGGING. CALL 1-800-632-4949 FOR BURIED UTILITY LOCATION SERVICE.
NORTH CAROLINA FIELD OFFICE:	LANDOWNER:	REVISIONS NO. BY DATE DESCRIPTION PROJECT #: SCALE:
SOIL&WATER ADDRESS:	ADDRESS:	1 DRAWN BY: DATE:
	ADDITION.	3 CHECKED BY: DATE:
CONSERVATION PHONE:		5 SHEET NO. 2 OF 3 FILENAME: RAINGARDEN2.DWG